

|                     |                         |                        |
|---------------------|-------------------------|------------------------|
| Gauge               | 1/10                    |                        |
| Manufacturing       | Level loop print        |                        |
| Pile description    | PA Luxus                |                        |
| Primary backing     | Woven                   |                        |
| Pile weight         | 220 gr/m <sup>2</sup>   |                        |
| Number of tufts     | 163.385 /m <sup>2</sup> |                        |
| Secondary backing   | Easyback                | Safeback               |
| Width               | 400 cm                  | 400 cm                 |
| Total weight        | 1000 gr/m <sup>2</sup>  | 1283 gr/m <sup>2</sup> |
| Total height        | 5 mm                    | 5 mm                   |
| Pile In/Out         | Out                     | Out                    |
| Roll length         | 40 m                    | 35 m                   |
| DOP                 | 1087#00558/16405/V      | 1087#00558/16405/C     |
| Fire classification | Efl                     | Efl                    |
| Use classification  | 22                      | 22                     |
| TOG rating          | 1                       | 0,9                    |

|                   |                   |     |
|-------------------|-------------------|-----|
| Available colours | Easyback   400 cm | 158 |
|                   | Safeback   400 cm | 158 |

Colour legend      158   Anthracite



These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.





158 - 400 cm